



Quick Check[®] 150 & 200 Series Bar Code Verifiers

The Quick Check 150 and 200 Series verifiers are compact, portable bar code verifiers that analyze bar code quality against traditional quality parameters and ANSI/CEN/ISO bar code print quality guidelines. All standard symbologies, including EAN/UPC with or without addenda, Code 39, Interleaved 2 of 5, Code 128, Codabar, MSI, and Code 16K are included with each unit.

QC150 and QC200 series verifiers are available in a variety of models that meet every portable verification requirement. The QC150 provides traditional pass/fail test results, and the QC200 series comes with a choice of industry application standards and provides traditional *and* sophisticated ANSI/CEN/ISO test results. The QC200 series also provides traditional and ANSI/CEN/ISO results without industry applications standards. Each model is available with a 5, 6, or 10 mil test aperture.

Regardless of the model you require, incorporating Quick Check verifiers into your quality control program assures that the bar codes you use comply with industry standards. This translates to improved efficiency and cost savings for your business.

QC150 and QC200 series verifiers are easy to use, and packed with high performance features that utilize the most sophisticated test methods. Every model can be instantly programmed to test specific bar code specifications by simply scanning command codes or by using the easy-to-follow menu-driven program that guides an operator through each step. Each model boosts productivity and is so inexpensive that you can afford to equip every technician involved in the bar code production and verification process.

Features & Benefits

Lightweight Pen Style Design

Choice of ANSI/CEN/ISO and Traditional Quality Parameters for all Standard Symbologies

Menu Driven for Easy Use

LCD and LEDs Display Test Results Instantly

Command Codes for Instant Programming

Each of these verifiers is designed to display bar code quality test results in one quick glance. Results are displayed immediately, and all the information needed for proper bar code evaluation is provided through an LCD and colored LEDs. To accommodate both right and left handed operators, the LCD image can be "flipped" for reading in either orientation.

For further detail, "scroll" and "select" buttons guide the user through an easy-to-follow menu to quickly display comprehensive test results. If needed, a detailed hard copy printout can be produced using an optional Quick Check printer or results can be sent to a PC via an RS-232 communication interface or the QCViewer software. Each verifier is powered by an integrated rechargeable battery pack.

Quick Check® 150 & 200 Series

Verification Methods

Parameters determined by ANSI/CEN/ISO bar code print quality guidelines and traditional pass/fail criteria. Refer to model matrix below for configurations.

	QC 150	QC 200	QC 210	QC 220	QC 230	QC 250
ANSI/CEN/ISO		X	X	X	X	X
Traditional	X	X	X	X	X	X
Industry Applications:						
SCC Retail			X	X	X	X
U.P.C. Coupon Code			X			X
AIAG (Automotive)					X	X
LOGMARS (Government)					X	X
HIBCC (Health)				X		X
SISAC (Serials coding)		X			X	
CTIA/ABCD (Computer)					X	X
Bookland (Books)			X			X
CCBBA (Blood bank)				X		X

Dimensions

Height:	1.6 in. (4.2 cm)
Width:	1.8 in. (4.6 cm)
Length:	7.1 in. (18.3 cm)

Mechanical

Weight:	5.5 ounces (156 g)
Power:	AC Charger
Case:	Lexan polycarbonate 141
Beeper:	A single beeper provides an audible valid/invalid signal and a triple beep on known out of spec codes
Display:	1 line X 12 character custom supertwist LCD with graphics
Keys:	Three conductive elastomer keys: power, scroll, and select
LED's:	Two LEDs: one red; one green

Environmental

Operating Temperature:	32 to 122° F (0 to 50° C)
Storage Temperature:	14 to 158° F (-20 to 70° C)
Relative Humidity:	5% to 95% Non-condensing

Optical

Test Aperture:	5, 6, or 10 mil
Scanner Illumination:	Visible : 660nm Infrared : 880nm

Symbologies

EAN/UPC with Addenda, Code 39, Interleaved 2 of 5, Codabar, Code 128, MSI, Code 16K, Regular 2 of 5 (Discrete /Industrial 2 of 5), IATA 2 of 5 (Straight 2 of 5)

Safety/Regulatory

FCC Class A, CE Certified

Features
Custom liquid crystal display (LCD)
LCD line scrolling
LCD image flip (left or right hand use)
Traditional test method
ANSI scan profile test method
Instant "On-Screen" ANSI grade
ANSI/CEN/ISO 10-scan grade averaging
Special reflectometer mode
Auto-discrimination of nine codes
"X" dimension determination
Detailed hard copy printout with optional printer
Automatic power off
Selectable beeper volume/pitch
Data buffer: 20 bar codes
Single Scan To Result (SSTR) menu



Worldwide Offices

Offices Serving North America

Skaneateles Falls, NY
Tel: (315) 685-8945
Fax: (315) 685-3172
Charlotte, NC
Tel: (704) 537-1444
Fax: (704) 532-4191

Offices Serving Europe, Middle East, and Africa

Europe
Tel: Int +31 (0) 40 24 24 486
Fax: Int +31 (0) 40 24 25 672
United Kingdom
Tel: Int +44 (0) 1 925 240055
Fax: Int +44 (0) 1 925 631280
France
Tel: Int +33 (0) 1 461 04111
Fax: Int +33 (0) 1 461 04120

Germany

Tel: Int +49 (0) 7 477 151377
Fax: Int +49 (0) 7 477 151378

Offices Serving Asia and the Pacific Rim

Hong Kong
Tel: Int +852 2511 3050/2511 3132
Fax: Int +852 2511 3557

Japan

Tel: Int +813 52127392
Fax: Int +813 32617372

Offices Serving Latin America

Naples, Florida
Tel: (941) 263-7600
Fax: (941) 263-9689

Web Site Address www.handheld.com

Welch Allyn Data Collection, Inc. and Hand Held Products, Inc. ("Hand Held Products") © 1999-2000, Hand Held Products. All rights reserved. Printed in the U.S.A.
Due to Hand Held Products' continuing product improvement programs, specifications and features herein are subject to change without notice.